

5MP FIXED LENS VIR MINI DOME

2592 X 1944:25FPS, 2.8/4MM LENS, 265+ VCOM/H.264, 120DB WDR, MULTI STREAM

Basic Series



KEY FEATURES

- 5 Megapixel Resolution
- 2592 x 1944:25fps
- 265+ Vcom/H.265/H.264/MJPEG
- Multi Streams
- Fixed Lens 2.8/4mm
- 120db WDR
- Corridor Mode 9:16
- Built-in Microphone
- Micro SD up to 256 GB
- 30m (98 ft) VIR Distance
- DC12V & PoE
- Weatherproof IP67
- Vandal Resistant IK10

Model No.	NV-FD15R3AC28	NV-FD15R3AC04
Sensor	5.0 Megapixel Progressive Scan CMOS	
Lens	2.8 @ F1.6	4mm @ F1.6
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Color: 0.003Lux (F1.6, AGC ON) 0Lux with IR	
Day/Night	IR-cut Filter with Auto Switch (ICR)	
Digital Noise Reduction	2D/3D DNR	
S/N	≥52 dB	
IR Range	Up to 30m (98ft) VIR Range	
Defog	Digital Defog Filter	
WDR	120db WDR	
Video		
Video Compression	265+ Vcom, H.265, H.264, MJPEG	
H.264 Code Profile	Baseline Profile, Main Profile, High Profile	
Frame Rate	Main Stream:5MP (2592 x 1944), Max 25fps; 4MP (2560 x 1440), Max 25fps; 3MP (2304 x 1296), Max 30fps; 2MP (1920 x 1080), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps	
BLD	Supported	
BLC	Supported	
9:16 Corridor Mode	Supported	
OSD	Up to 4 OSDs	
Privacy Mask	Up to 8 areas	
ROI	Up to 2 areas	
Motion Detection	Up to 4 areas	
Network		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP	
System Compatibility	Onvif (Profile S, G, T), API	
Storage		
Network	1 RJ45 10M/100M Base-TX Ethernet	
Built-In Microphone	Supported	
Interface		
Network	1 RJ45 10M/100M Base-TX Ethernet	
Built-In Microphone	Supported	
General		
Power	DC 12V±25%, PoE (IEEE 802.3af)	Power Consumption: Max 4.5W
Dimensions (W x H)	109 x 81mm(4.3"x3.2")	
Weight	0.37kg(0.81lb)	
Working Environment	-30°C~60°C(-22°F~140°F), Humidity:≤95%RH (Non-condensing)	
Ingress Protection	IP67	
Vandal Resistant	IK10	

5MP FIXED LENS VIR MINI DOME

2592 X 1944:25FPS, 2.8/4MM LENS, 265+ VCOM/H.264, 120DB WDR, MULTI STREAM

Product Details	
Part Code	NV-FD15R3AC28
Description	5MP Dome, 2880 x 1620:25fps, 265+ Vcom/H.264, Multi Stream, Fixed Lens 2.8mm, 30m VIR, 3-Axis, Micro SD Card Slot, 12V & PoE, BLD, 120db WDR, IP67 & IK10, Mic
Part Code	NV-FD15R3AC04
Description	5MP Dome, 2880 x 1620:25fps, 265+ Vcom/H.264, Multi Stream, Fixed Lens 4.0mm, 30m VIR, 3-Axis, Micro SD Card Slot, 12V & PoE, BLD, 120db WDR, IP67 & IK10, Mic

DIMENSIONS

