

Basic Series



KEY FEATURES

- 5 Megapixel Resolution
- 2880 x 1620:25fps
- 265+ Vcom/H.265/H.264/MJPEG
- Multi Stream
- 2.8 ~ 12mm Motorized Zoom Lens
- 120db WDR
- Micro SD Card Slot
- Corridor Mode
- Built-in Microphone
- IR Range: up to 50m (164 ft)
- DC12V & PoE
- Weatherproof IP67 & IK10

| | | |
|-------------------------|---|---------------------------|
| Model No. | NV-ZB15R5AC12 | |
| Sensor | 5.0 Megapixel, Progressive Scan, CMOS | |
| Lens | 2.8 ~ 12mm Motorized Zoom Lens | |
| Shutter | Auto/Manual, 1 ~ 1/100000s | |
| Minimum Illumination | Colour: 0.003 Lux (F1.6, AGC ON) 0 Lux with IR on | |
| Day/Night | IR-cut Filter with Auto Switch (ICR) | |
| Digital Noise Reduction | 2D/3D DNR | |
| S/N | ≥52 dB | |
| IR Range | Up to 50m (164ft) VIR Range | |
| WDR | 120db WDR | |
| Video | | |
| Video Compression | Vcom H.265+, H.264, MJPEG | |
| H.264 Code Profile | Baseline Profile, Main Profile, High Profile | |
| Frame Rate | Main Stream: 5MP (2880 x 1620), Max 25fps; 4MP (2560 x 1440), Max 25fps; 3MP (2304 x 1296), Max 30fps; 1080P (1920 x 1080), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360, Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps | |
| BLD | Supported | |
| BLC | Supported | |
| XLight | Supported | |
| Corridor Mode | Supported | |
| OSD | Up to 4 OSDs | |
| Privacy Mask | Up to 4 areas | |
| ROI | Up to 8 areas | |
| Motion Detection | Up to 4 areas | |
| Network | | |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, | |
| Interface | | |
| Network | 1 RJ45 10M/100M Base-TX Ethernet | |
| Built-in Microphone | Supported | |
| Storage | | |
| Edge Storage | MicroSD, up to 256GB | |
| Network Storage | ANR | |
| General | | |
| Power | DC 12V±25%, PoE (IEEE 802.3af) | Power Consumption: Max 7W |
| Dimensions (L x W x H) | 206 x 74 x 74mm (8.1" x 2.9" x 2.9") | |
| Weight | 0.55kg (1.2lb) | |
| Working Environment | -30°C ~ +60°C (-22°F ~ 140°F), Humidity :10%~90% RH(Non-condensing) | |
| Ingress Protection | IP67 | |
| Product Details | | |
| Part Code | NV-ZB15R5AC12 | |
| Description | 5MP Bullet, 2880 x 1620:25fps, 265+ Vcom/H.264, Multi Stream, 2.8~12mm Motorized Lens, SD Card Slot, 50m VIR, 12V & PoE, BLD, 120db WDR, IP67, Mic | |

DIMENSIONS

