



2MP OUTDOOR FIXED NETWORK MINI BULLET

1920 X 1280:30FPS, 2.8/4MM FIXED LENS, 265+ VCOM/H.265, TRUE WDR, TRIPLE STREAM

Sterling Series



KEY FEATURES

- 2 Megapixel Camera
- 1920 x 1080:30fps
- Fixed Lens 2.8/4mm
- 9:16 Corridor Mode
- 265+ Vcom/H.265/H.264/MJPEG
- Triple Streams
- IR, up to 40m (131 ft) VIR
- XLight
- Built-in Microphone
- SD Card Slot
- DC12V & PoE
- Weatherproof IP67

Model No.	NV-FB22R4AC28	NV-FB22R4AC40
Sensor	2.0 Megapixel, Progressive Scan, CMOS	
Lens	2.8 @ F1.6	4mm @ F1.6
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR on	
Day/Night	IR-cut Filter with Auto Switch (ICR)	
Digital Noise Reduction	2D/3D DNR	
S/N	≥52 dB	
IR Range	Up to 40m (131ft) VIR Range	
Defog	Digital Defog	
WDR	120db	
Video		
Video Compression	265+ Vcom, H.265, H.264, MJPEG	
H.264 Code Profile	Baseline Profile, Main Profile, High Profile	
Frame Rate	Main Stream: 2MP (1920 x 1080), Max 30fps Sub Stream: 2MP (1920 x 1080), Max 30fps Third Stream: D1 (720 x 576), Max 30fps	
9:16 Corridor Mode	Supported	
BLD	Supported (Bright Light Dispersion)	
BLC	Supported	
OSD	Up to 8 OSDs	
Privacy Mask	Up to 4 areas	
ROI	Up to 8 areas	
Motion Detection	Up to 4 areas	
Network		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS	
System Compatibility	Onvif (Profile S, T), API	
Interface		
Network	1 RJ45 10M/100M Base-TX Ethernet	
Built-in Mic	Supported	
Storage		
Edge Storage	Micro SD, up to 256GB	
Network Storage	ANR	
General		
Power	DC 12V±25%, PoE (IEEE 802.3af)	Power Consumption: Max 6W
Dimensions (W x H x L)	155.9 x 63.1 x 62.7mm (6.1" x 2.5" x 2.5")	
Weight	0.42kg (0.93lb)	
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (Non-condensing)	
Ingress Protection	IP67	

Product Details	
Part Code	NV-FB22R4AC28
Description	2MP Bullet, 1920 x 1080:30fps, 265+ Vcom/H.264, Triple Stream, Fixed Lens 2.8mm, 40m VIR, XLight, 120dB WDR, SD Card Slot, BLD, 12V & PoE, IP67, Mic
Part Code	NV-FB22R4AC40
Description	2MP Bullet, 1920 x 1080:30fps, 265+ Vcom/H.264, Triple Stream, Fixed Lens 4.0mm, 40m VIR, XLight, 120dB WDR, SD Card Slot, BLD, 12V & PoE, IP67, Mic

DIMENSIONS

