

Sterling Series



KEY FEATURES

- 2 Megapixel Resolution
- 1920 x 1080:30fps
- 5x (2.7 ~ 13.5mm) Motorized Lens
- 120dB WDR
- 2D/3D DNR
- 265+ Vcom, H.265, H.264, MJPEG
- Triple Streams
- 9:16 Corridor Mode
- VIR, 50m(164 ft) IR Distance
- XLight
- Alarm I/O
- Audio I/O
- MicroSD Card Support
- PoE
- IP67
- IK10

Model No.	NV-ZB22R5VCT13	
Sensor	2.0 Megapixel, Progressive Scan, CMOS	
Lens	2.7 ~ 13.5mm, AF Automatic Focusing and Motorized Zoom Lens	
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Colour: 0.0001Lux (F1.2, AGC ON) 0Lux with IR on	
Day/Night	IR-cut Filter with Auto Switch (ICR)	
Digital Noise Reduction	2D/3D DNR	
S/N	≥52 dB	
IR Range	Up to 50m (164ft) IR Range	
Defog	Digital Defog Filter	
WDR	120dB	
Video		
Video Compression	265+ Vcom, H.265, H.264, MJPEG	
H.264 Code Profile	Baseline Profile, Main Profile, High Profile	
Frame Rate	Main Stream: 2MP (1920 x 1080), Max 30fps; 720P (1280 x 720), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360, Max 30fps; 2CIF(704x 288), Max 30fps; CIF(352 x 288), Max 30fps Third Stream: D1 (720 x 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps	
BLD	Supported	
BLC	Supported	
9:16 Corridor Mode	Supported	
XLight	Supported	
OSD	Up to 8 OSDs	
Privacy Mask	Up to 4 areas	
ROI	Up to 8 areas	
Motion Detection	Up to 4 areas	
Storage		
Edge Storage	Micro SD Card Supported up to 256GB	
Network Storage	ANR, NAS(NFS)	
Network		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS	
System Compatibility	Onvif (Profile S, G,) API	
Interface		
Network	1 RJ45 10M/100M Base-TX Ethernet	
Audio I/O	Input: Impedance 35kΩ; Amplitude 1V [p-p] Output: Impedance 600Ω; Amplitude 1V [p-p]	
Alarm I/O	1/1	
General		
Power	DC 12V±25%, PoE (IEEE 802.3af)	Power Consumption: Max 8.5W
Dimensions (L x W x H)	245.4 x 85.4 x 86.4mm (9.7" x 3.4" x 3.4")	
Weight	0.92kg (2.03lb)	
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (Non-condensing)	

Ingress Protection	IP67
Vandal Resistant	IK10
Product Details	
Part Code	NV-ZB22R5VCT13
Description	2MP Bullet, 1920 x 1080:30fps, 265+ Vcom/H.264, Triple Streams, 2.7~13.5mm Motorized Lens, Alarm I/O, Audio I/O, 50m VIR, XLight, 120dB WDR, SD Card Slot, BLD, 12V & PoE, IP67

DIMENSIONS

