

Sterling Series



## KEY FEATURES

- 5 Megapixel Resolution
- 2880 x 1620:30fps
- 265+ Vcom/H.265/H.264/MJPEG
- Triple Stream
- 120db WDR
- 2.8mm/4.0mm Lens
- SD Card Slot
- Built-in Microphone
- Built-in Speaker
- Alarm Light
- DC12V & PoE
- IR Range: up to 30m (98ft) VIR
- XLight Technology
- Weatherproof IP67

Model No.	NV-FB25R3ACT28	NV-FB25R3ACT04
Sensor	1/2.7", 5.0 Megapixel, Progressive Scan, CMOS	
Lens	2.8mm @F2.0	4.0mm @F2.0
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on	
Day/Night	IR-cut Filter with Auto Switch (ICR)	
Digital Noise Reduction	2D/3D DNR	
S/N	≥56 dB	
IR Range	Up to 30m (98ft) IR Range	
Defog	Digital Defog Filter	
WDR	120dB	
<b>Video</b>		
Video Compression	265+ Vcom, H.265, H.264, MJPEG	
H.264 Code Profile	Baseline Profile, Main Profile, High Profile	
Frame Rate	Main Stream:5MP (2880 x 1620), Max 30fps; 4MP (2560 x 1440), Max 30fps; 3MP (2304 x 1296), Max 30fps; 1080P (1920 x 1080), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps Third Stream: D1 (720 x 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps	
BLD	Supported	
BLC	Supported	
9:16 Corridor Mode	Supported	
OSD	Up to 4 OSDs	
Privacy Mask	Up to 4 areas	
ROI	Up to 2 areas	
Motion Detection	Up to 4 areas	
<b>Audio</b>		
Audio Compression	G.711	
Suppression	Supported	
Sampling Rate	8kHz	
<b>Storage</b>		
Edge Storage	Micro SD, up to 256GB	
Network Storage	ANR	
<b>Network</b>		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, sSNMP, QoS	
System Compatibility	Onvif (Profile S, T), API	
<b>Interface</b>		
Network	1 RJ45 10M/100M Base-TX Ethernet	
Built-In Microphone	Supported	
Built-in Speaker	Supported	
Alarm Light	Supported	

# 5MP OUTDOOR FIXED MINI BULLET CAMERA

2880 X 1620:30FPS, 2.8/4MM FIXED LENS, 265+ VCOM/H.265, TRUE WDR, TRIPLE STREAM

General		
Power	DC 12V±25%, PoE (IEEE 802.3af)	Power Consumption: Max 11.5W
Dimensions (L x W x H)	191 x 75 x 74mm (7.5" x 3.0" x 2.9")	
Weight	0.45kg (0.99lb)	
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (Non-condensing)	
Ingress Protection	IP67	
Product Details		
Part Code	NV-FB25R3ACT28	
Description	5MP Fixed Bullet, 2880 x 1620: 30fps, 265+ Vcom/H.264, Triple Stream, 120dB WDR, Fixed Lens 2.8mm, Alarm Light, SD Card Slot, 30m VIR, XLight, 12V & PoE, BLD, IP67 & IK10, Mic & Speaker	
Part Code	NV-FB25R3ACT04	
Description	5MP Fixed Bullet, 2880 x 1620: 30fps, 265+ Vcom/H.264, Triple Stream, 120dB WDR, Fixed Lens 4.0mm, Alarm Light, SD Card Slot, 30m VIR, XLight, 12V & PoE, BLD, IP67 & IK10, Mic & Speaker	

## DIMENSIONS

