

Sterling Series



KEY FEATURES

- 5 Megapixel Resolution
- 2880 x 1620:30fps
- 5x (2.7 ~ 13.5mm) Motorized Lens
- 120dB WDR
- 2D/3D DNR
- 265+ Vcom, H.265, H.264, MJPEG
- Triple Streams
- 9:16 Corridor Mode
- VIR, 50m(164 ft) IR Distance
- XLight
- Alarm I/O
- Audio I/O
- 256G MicroSD Card Support
- PoE
- IP67
- IK10

Model No.	NV-ZB25R5VCT13
Sensor	5.0 Megapixel, Progressive Scan, CMOS
Lens	2.7 ~ 13.5mm, AF Automatic Focusing and Motorized Zoom Lens
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.0001Lux (F1.2, AGC ON) 0Lux with IR
Day/Night	IR-cut Filter with Auto Switch (ICR)
Digital Noise Reduction	2D/3D DNR
S/N	≥52 dB
IR Range	Up to 50m (164ft) VIR Range
Defog	Digital Defog Filter
WDR	120db
Video	
Video Compression	265+ Vcom, H.265, H.264, MJPEG
H.264 Code Profile	Baseline Profile, Main Profile, High Profile
Frame Rate	Main Stream:5MP (2880 x 1620), Max 30fps; 4MP (2560 x 1440), Max 30fps; 3MP (2304 x 1296), Max 30fps; 1080P (1920 x 1080), Max 30fps Sub Stream: 720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps Third Stream: D1 (720 x 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps;
BLD	Supported
BLC	Supported
9:16 Corridor Mode	Supported
XLight	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8kHz
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
System Compatibility	Onvif (Profile S, G, T), API
Interface	
Audio I/O	Input: Impedance 35kΩ; Amplitude 2V [p-p] Output: Impedance 600Ω; Amplitude 2V [p-p]
Alarm I/O	1/1
Network	1 RJ45 10M/100M Base-TX Ethernet

5MP MOTORIZED XLIGHT VIR BULLET CAMERA

2880 X 1620:30, 50M VIR, 5X(2.7~13.5MM) MOTORIZED LENS, TRUE WDR, TRIPLE STREAM

General		
Power	DC 12V±25%, PoE (IEEE 802.3af)	Power Consumption: Max 10W
Dimensions (L x W x H)	245 x 86 x 85mm (9.6" x 3.4" x 3.3")	
Weight	1.0kg (2.2lb)	
Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (Non-condensing)	
Ingress Protection	IP67	
Product Details		
Part Code	NV-ZB25R5VCT13	
Description	5MP Bullet, 2880 x 1620:30, 265+ Vcom/H.264, Triple Streams, 2.7~13.5mm Motorized Lens, Alarm I/O, Audio I/O, 50m VIR, XLight, 120dB WDR, SD Card Slot, BLD, 12V & PoE, IP67	

DIMENSIONS

