

Meta Series



KEY FEATURES

- 32/64 Channel Input
- Support 265+ Vcom/H.265/H.264 Video Formats
- Third-party IP Cameras Supported with Onvif Conformance
- Support Dual HDMI, 1 Channel VGA, HDMI at up to 4K (3840 x 2160) Resolution
- Up to 12 Megapixels Resolution Recording
- 8 SATA HDDs, up to 10TB for each HDD
- Dual Gigabit Network Interface
- Alarm I/O
- Audio I/O
- ANR Technology to enhance the storage reliability when the network is disconnected
- LPR Supported
- Support N+1 Hot Spare
- Support Export System Log

Model No.	MN3208KR	MN6408KR
IP Video Input	32 Channel	64 Channel
Two-Way Audio Input	1 Channel, RCA	
Video		
Incoming Bandwidth	256Mbps	320Mbps
Outgoing Bandwidth	256Mbps	
Remote Users	8	
Protocols	IPV4, IPV6, SNMP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, SMTP, TCP/IP, RTSP	
Video/Audio Output		
HDMI	1920 x 1080p/60Hz, 1920 x 1080p/50Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz	
HDMI 2	4K (3840 x 2160)/30Hz, 1920 x 1080p/60Hz, 1920 x 1080p/50Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz	
VGA Output	1920 x 1080p/60Hz, 1920 x 1080p/50Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz	
Recording Resolution	12MP/ 8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/D1/ 2CIF/ CIF	
Audio Output	1 Channel, RCA	
Audio Input	1 Channel, RCA	
Synchronous Playback	16/9/4/1 Channel	
Corridor Mode Screen	3/4/5/7/9/10/12/16 (16 Channel)	3/4/5/7/9/10/12/16/25/36 (32 Channel)
Decoding		
Decoding Format	265+ Vcom, H.265, H.264	
Live view/ Playback	12MP/ 8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/ D1/ 2CIF/ CIF	
Capability	12MP@25, 4K@30, 4MP@30, 1080P@30, 960P@25, 720P@30, D1	
Hard Disk		
SATA	8 SATA Interfaces	
Capacity	Up to 10TB for each HDD	
External Interface		
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface	
USB Interface	Front Panel: 2 x USB2.0, Rear Panel: 1 x USB3.0	
RS232	Supported Port for PTZ	
RS485	Supported Port for Console	
RS485	Supported Port for Keyboard	
Alarm In	16 Channel	
Alarm Out	4 Channel	
General		
Power Supply	AC100V~240V50Hz~60Hz, Consumption ≤15W (Without HDD)	
Working Environment	-10°C ~ +55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(Non-condensing)	
Dimensions(W x D x H)	440mm(W) x 320mm(D) x 66.8mm(H)	
Weight (without HDD)	4.1Kg	

Product Details	
Part Code	MN3208KR
Description	META Series, 32 Channel, 8 SATA Interface (10TB Each Slot Support), 1 eSATA, RAID5/6/10, 256Mbps Input, 256Mbps Output, 2HDMI 4K Output, 2VGA, Audio I/O, Alarm I/O, 2 x RJ45, AC100-240V
Part Code	MN6408KR
Description	META Series, 64 Channel, 8 SATA Interface (10TB Each Slot Support), 1 eSATA, RAID5/6/10, 320Mbps Input, 256Mbps Output, 2HDMI 4K Output, 2VGA, Audio I/O, Alarm I/O, 2 x RJ45, AC100-240V

REAR PANEL



DIMENSIONS

