

META Series



KEY FEATURES

- 8 Megapixel Resolution
- 3840 x 2160:30fps
- Fixed Lens 2.7~13.5mm
- 265+ Vcom/H.265/H.264/MJPEG
- 120db WDR
- Triple Streams
- Up to 60m (196.85 ft) VIR
- XLight
- Alarm I/O
- Audio I/O
- ONVIF S, T, G & Q
- MicroSD Card Slot
- PoE(802.3af)
- DC12V ±10%
- Weatherproof IP67
- Vandal Resistant IK10

XLight Vpix VIR Vcom



SD Card



Optical Zoom



PoE



Onvif



Multi Streams



Motion Detection



IR



IP67



WDR




Smart Features




Model No.	MB8X5R6VTC
Sensor	1/2.8" Progressive Scan CMOS 8.0 Megapixel
Lens	2.7~13.5mm @ F1.4
Field of View	H96°~H33°/ D112°~D37°/ V53°~V18°
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.003Lux (F1.4, AGC ON) 0Lux with IR on
Day/Night	IR-cut Filter with Auto Switch (ICR)
Digital Noise Reduction	2D/3D DNR
S/N	≥55 dB
IR Range	Up to 60m (196.85ft) VIR Range
Defog	Digital Defog
WDR	120db
Video	
Video Compression	265+ Vcom, H.265, H.264, MJPEG
H.264 Code Profile	Baseline Profile, Main Profile, High Profile
Frame Rate	Main Stream: 8MP (3840 x 2160, 3072 x 2048, 2592 x 1944, 2592 x 1520, 2048 x 1536, 1920 x 1080, 1280 x 960, 1280 x 720, 704 x 576:30fps Sub Stream: D1 704 x 576, 640 x 480, 640 x 360, 352 x 288 Max 30fps Third Stream:1MP 1280 x 720, 704 x 576, 640 x 480, 640 x 360, 352 x 288 Max 30fps
Bit Rate	16Kbps~16Mbps (CBR/VBR)
9:16 Corridor Mode	Supported
BLD	Supported (Bright Light Dispersion)
BLC	Supported
XLight	Supported
OSD	Supported
Privacy Mask	Up to 8 areas
ROI	Up to 8 areas
Motion Detection	Supported
Network	
Protocols	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
System Compatibility	ONVIF Profile G & Q & S & T, API
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
Alarm I/O	1/1
Audio I/O	1/1
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	NAS (NFS, SMB / CIFS), ANR

Smart Function	
Intelligent Detection	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed People Counting & Report
General	
Power	PoE (802.3af) / DC12V ± 10%
Power Consumption:	Max 11W With IR On
Dimensions (H x W x L)	134mm x 126mm x 285mm
Weight	1080g (2.38lb)
Ingress Protection	IP67
Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (Non-condensing)
Product Details	
Part Code	MB8X5R6VTC
Description	META Series, Bullet, 8MP(3840 x 2160:25/30fps), Motorized Zoom Lens (2.7~13.5mm), VIR Range up to 60m, Audio I/O, Alarm I/O, Micro SD Card Slot, 120db WDR, DC12V/PoE(802.3af), IP67, Built-in AI Function

DIMENSIONS



ACCESSORIES

<p>Pole Mount Bracket Model No.: VN-MPM01</p> 	<p>Corner Mount Bracket Model No.: VN-MCM01</p> 	<p>Wall Mount Bracket Model No.: VN-MJB01</p> 
---	---	---