



5MP 5X ZOOM LENS LPR BULLET

2592 X 1944:30FPS, 2.7~13.5MM LENS, 265+ VCOM/H.265, TRUE WDR, TRIPLE STREAM

XLight Vpix VIR Vcom



SD Card



Optical Zoom



PoE



Onvif



Multi Streams



Motion Detection



IR



IP67



WDR



LPR

Specialized Series




KEY FEATURES

- 5 Megapixel Resolution
- 2592 x 1944:30fps
- Motorized Lens 2.7~13.5mm
- 265+ Vcom/H.265/H.264/MJPEG
- 120db WDR
- Triple Streams
- Up to 50m (164 ft) VIR
- XLight
- Alarm I/O
- Audio I/O
- ONVIF S, T, G & Q
- License Plate Recognition
- MicroSD Card Slot
- PoE(802.3af)
- DC12V ±10%
- Weatherproof IP67
- Vandal Resistant IK10




Model No.	SB5X5R5VTCLP
Sensor	1/2.8" Progressive Scan CMOS 5.0 Megapixel
Lens	2.7~13.5mm @ F1.4
Field of View	H99°~H31°/ D124°~D38°/V72°~V23°
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.001Lux (F1.4, AGC ON), 0Lux with IR on
Day/Night	IR-cut Filter with Auto Switch (ICR)
Digital Noise Reduction	2D/3D DNR
S/N	≥55 dB
IR Range	Up to 50m (164 ft) VIR Range
Defog	Digital Defog
WDR	120db
Video	
Video Compression	265+ Vcom, H.265, H.264, MJPEG
H.264 Code Profile	Baseline Profile, Main Profile, High Profile
Frame Rate	Main Stream: 5MP 2592 x 1944, 2048 x 1536, 1920 x 1080, 1280 x 960, 1280 x 720, 704 x 576 Max 30fps Sub Stream: D1 704 x 576, 640 x 480, 640 x 360, 352 x 288 Max 30fps Third Stream: 2MP 1920 x 1080 1280 x 720, 704 x 576, 640 x 480, 640 x 360, 352 x 288 Max 30fps
Bit Rate	16Kbps~16Mbps (CBR/VBR)
9:16 Corridor Mode	Supported
BLD	Supported (Bright Light Dispersion)
BLC	Supported
XLight	Supported
OSD	Supported
Privacy Mask	Up to 8 areas
ROI	Up to 8 areas
Motion Detection	Supported
Network	
Protocols	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
System Compatibility	ONVIF Profile G & Q & S & T, API
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
Alarm I/O	1/1
Audio I/O	1/1
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	NAS (NFS, SMB / CIFS), ANR

Smart Function	
LPR Speed	200km/h
Recognition Accuracy	>95%
Database	Up to 1000 records inside the camera
Coverage	4 Zone (Simultaneous)
General	
Power	PoE (802.3af) / DC12V ± 10%
Power Consumption:	Max 9W With IR On
Dimensions (Φ x L)	Φ76mm x 239.5mm
Weight	1080g (2.38lb)
Ingress Protection	IP67
Vandal Resistant	IK10
Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (Non-condensing)
Product Details	
Part Code	SB5X5R5VTCLP
Description	Super AI Series, Bullet, 2MP(1920 x 1080:25/30fps), Motorized Zoom Lens(2.7~13.5mm), VIR Range up to 50m, Audio I/O, Alarm I/O, Micro SD Card Slot, 120db WDR, DC12V/PoE(802.3af), IP67, Built-in LPR & AI Function

DIMENSIONS



ACCESSORIES

<p>Pole Mount Bracket Model No.: VN-MPM01</p> 	<p>Corner Mount Bracket Model No.: VN-MCM01</p> 	<p>Wall Mount Bracket Model No.: VN-MJB02</p> 
---	---	---